

ISO/IEC 15693 Protocol HF Tag Reader



Model: RR9037SR-B

Size: 122mmx87mmx23mm

Weight: 111g

GENERAL DESCRIPTION

RR9037SR-B is a high performance ISO/IEC15693 protocol HF tag reader. It is designed upon fully self-intellectual property and supports fast tag read/write operation with high identification rate. It can be widely applied in many RFID application systems such as logistics, personnel identification, conference attendance system, access control, anti-counterfeit and industrial production process control system.

FEATURES

- Self-intellectual property;
- Support mainstream ISO/IEC15693 protocol tag (TI, PHILIPS, ST, INFINEON, FUJITSU, EM...);
- Advanced tag processing algorithm, high identification rate;
- Built-in TX/RX antenna with effective distance up to 150mm^{*};
- Support Scan-mode^①;
- Support RS232 interface;
- Low power dissipation design with single DC+12V power source needed;
- Provide DLL and demonstration software to facilitate development.

①Scan-mode: It refers to reader's automatic working mode.

CHARACTERISTICS

- Absolute Maximum Rating

ITEM	SYMBOL	VALUE	UNIT
Power Supply	VCC	12	V
Operating Temp.	T _{OPR}	-10~+60	°C
Storage Temp.	T _{STR}	-25~+80	°C

- Electrical and Mechanical Specification

Under T_A=25°C, VCC=+12V unless specified

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Power Supply	VCC	11.5	12	15	V
Current Dissipation	I _C		90	150	mA
Frequency	F _{REQ}		13.56		MHz
Effective Distance [*]	DIS	0	100	150	mm

^{*}Effective distance depends on tag and working environment.

Remark:

1. Specifications are subject to change, please pay attention to our latest one.

2. Shenzhen RoyalRay Science and Technology Co., Ltd. reserves the right to the final interpretation of the above terms.

Page2 Total2

Shenzhen RoyalRay Science and Technology Co., Ltd.

www.rr-rfid.com

Add: Rm.116, Luohu Science & Technology Bldg., No.85 Taining Rd., Shenzhen, P.R.C.

Tel: +86 755 25531562 25636705

Fax: +86 755 25531562

E-Mail: market@rr-rfid.com